

MARKED-UP VERSION OF SUBSTITUTE SPECIFICATION

TITLE OF THE INVENTION

[0001] Appliance for Water-Jet Surgery

DESCRIPTION

CROSS-REFERENCE TO RELATED APPLICATIONS

[0002] This application is a Section 371 of International Application No. PCT/EP2005/002917, filed March 18, 2005, which was published in the German language on October 27, 2005, under International Publication No. WO 2005/099595 A1 and the disclosure of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0003] The invention relates to an appliance for water-jet surgery, in which a fluid is expelled from a nozzle under high pressure for the selective cutting of tissue.

[0004] Customarily in the case of such an appliance a supply cylinder having an (initially closed) outlet at one end is filled with a working fluid, such as Ringer solution, and at its other end is closed by means of a piston. This supply cylinder is then inserted into a stably positioned chamber in an appliance housing. After closure of the housing an actuating rod driven by a hydraulic cylinder is placed in contact with the piston in the supply cylinder. Now the known appliance is ready for operation. During operation the pressure that must be applied to the fluid is generated by the hydraulic cylinder.

[0005] So that during an operation a sufficient amount of working fluid is available with no need to exchange the supply cylinder, a procedure that would involve a not inconsiderable interruption of the operation, the supply cylinder must have a relatively large volume. The larger the cylinder bore is made, the larger must be the force exerted by the hydraulic system, and hence a correspondingly greater stability is required of the receptacle for the supply cylinder. On the other hand, if the volume of the supply cylinder is increased by lengthening it, and hence lengthening the stroke of the piston, the result is an increase in the overall height of the appliance. The present-day compromise has produced supply cylinders with a diameter of ca. 60 mm, with the result that the associated appliances are constructed as stands and have a height of ca. 1,200 to 1,500 mm. The necessary actuation devices, i.e. the hydraulic cylinder along with the associated hydraulic pump, are extremely elaborate and very awkward to use.

[0006] Furthermore, in the case of “small” operations for which only a slight amount of fluid is used, the excess working fluid must be discarded because of the sterility requirements for a working fluid, which increases the operating costs of the known appliance.

BRIEF SUMMARY OF THE INVENTION

5 [0007] It is the ~~objective~~object of the invention to ~~disclose~~provide a simple appliance that enables economical operation while reducing the structural complexity.

[0008] ~~This objective is achieved in the case of~~According to the present invention there is provided an appliance for water-jet surgery ~~by providing~~comprising a plurality of supply ~~cylinders, in which~~cylinder and piston arrangements each defining an outlet and adapted to store a working fluid ~~is stored and from which the fluid that~~can be expelled, ~~by means of the piston, through an~~said outlet ~~into~~; a pressure conduit, ~~by means of a piston in communication with said outlets and into which said working fluid is expelled.~~ At least one actuation device is provided to actuate the pistons. In addition, a change-over device is provided ~~by means of which~~to shift the actuation ~~is shifted~~ from the piston of
10
15 one supply cylinder to the piston of another supply cylinder, so that the working fluid can be expelled into the pressure conduit from the supply cylinders one after another, as they are consecutively emptied.

[0009] ~~Thus an essential point~~The basis of the invention resides in the fact that the ~~one (single)~~ supply cylinder previously provided is here subdivided into a plurality of
20 correspondingly smaller supply cylinders. This measure solves several problems simultaneously. First, because of their reduced diameter the smaller supply cylinders can be made of a weaker material, which nevertheless can resist the prevailing ~~(very)~~ high pressures. Second, the ~~necessary~~required working pressure can be produced with less force, so that the necessary actuation devices can be more simply constructed. Third, the appliance can be made very much
25 smaller, ~~(e.g., can be set onto a table)~~, on account of the smaller stroke of the pistons. And fourth, during a “relatively small” operation fewer supply cylinders are used up than in a “larger” operation; in the present appliance, the supply cylinders that have not been used are available for a subsequent operation, as their sterility is still ensured.

[0010] Preferably the change-over device is so constructed that there is some overlap between
30 the consecutive periods during which pistons are actuated, so that the expulsion of fluid into the pressure conduit produced by their actuation is uninterrupted. Whereas on one hand, in the case of the conventional large-volume supply cylinders, such an uninterrupted supply of working fluid is

ensured by the large fluid volume, with the present invention this uninterrupted supply of fluid is very efficiently achieved.

[0011] Preferably sealing devices are provided to make the fluid outlet on the supply cylinder water-tight, so that no manual coupling is needed for a firm connection; instead, a forceful automatic/mechanical coupling of the supply cylinder to the sealing device suffices.

[0012] An overlapping actuation of the pistons is especially simple when a plurality of actuation devices is provided. Then there is no need to move the actuation devices from one piston to the next; when the number of actuation devices corresponds to the number of supply cylinders in the device, a simple (electronic) control means can implement the change-over. However, it is also possible to work with a smaller number of actuation devices (only one, in the minimal case) if the change-over device ensures that the actuation device is always guided to the next in a sequence of new supply cylinders.

[0013] The pistons are preferably provided with back-flow barriers, such that after working fluid has been ejected by a piston, the piston cannot be pushed back into a previous position from the position it has reached, in particular from its final position after all the working fluid has been ejected. By this means it can be ensured that refilling is prevented and hence the possibility of working with unsterile medium can be reliably eliminated.

[0014] At the outlet of the supply cylinder an irreversibly openable transport gasket is preferably provided. This measure likewise makes it possible for the use of unsterile medium to be prevented. Furthermore, such an irreversibly openable transport gasket can be very simply constructed and designed in such a way that it opens automatically when a supply cylinder is put into place or when it is first actuated. Because of the very high pressures employed here, it is possible also to construct the transport gasket so that it opens automatically when pressure is first applied.

[0015] Preferably a change-over magazine is provided, which accommodates a group of supply cylinders. This makes handling of the apparatus particularly simple, both during the insertion of multiple supply cylinders into the appliance and when individual actuation devices are being changed over from one supply cylinder to another. The change-over magazine preferably comprises chambers that closely surround the supply cylinders. In this case the supply cylinders can be constructed with an especially thin wall, which expands somewhat as the pressure builds up and then becomes apposed to the walls of the change-over magazine. The receptacle can also be made with sufficient shape stability to withstand the pressure without becoming form-fitted to the housing.

[0016] In the change-over magazine collection devices are preferably provided, to guide the working fluid from several supply cylinders to the pressure conduit. This is especially advantageous when the working fluid is being conducted in an overlapping manner from various supply cylinders.

[0017] Preferably ventilation devices are provided, in particular to remove air simultaneously from conduit sections between the outlets of the supply cylinders and the pressure conduit, so that there is no interruption or pulsation of the working fluid associated with the release of air remnants. Preferably the ventilation devices are disposed in the change-over magazine.

[0018] In one embodiment of the invention the change-over magazine is fixedly connected to the pressure conduit and is intended to be used only once. In this case the change-over magazine can already be filled with supply cylinders by the manufacturer, so that although the advantage of saving working liquid (as well as the supply cylinders) is no longer obtained, all the other advantages cited above are nevertheless preserved. A special advantage in this case is the ease of manipulation, in particular with regard to sterility criteria.

~~[0019] Preferred embodiments of the invention will be apparent from the subordinate claims and the following exemplary embodiments, which are explained in greater detail with reference to drawings, wherein~~

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0020] The foregoing summary, as well as the following detailed description of the invention, will be better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, there are shown in the drawings embodiments which are presently preferred. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown.

[0021] In the drawings:

[0022] Fig. 1 is a schematic sectional drawing of a first embodiment of the invention with inserted magazine, prior to actuation,

[0023] Fig. 2 shows the arrangement according to Fig. 1 during the initial phase of actuation of one cylinder,

[0024] Fig. 3 shows the previously illustrated arrangement during the expulsion of working fluid,

[0025] Fig. 4 shows the previously illustrated arrangement when one supply cylinder is empty and another supply cylinder is being actuated,

[0026] Fig. 5 is a perspective drawing of part of the arrangement according to Figs. 1 - 4,
[0027] Fig. 6 is a perspective drawing of part of another embodiment of the invention,
[0028] Fig. 7 is an exploded drawing of part of the arrangement according to Fig. 6, and
[0029] Fig. 8 is a schematic drawing of a control means for the arrangement according to
5 Figs. 1 - 5.

DETAILED DESCRIPTION OF THE INVENTION

[0030] In the following description, the same reference numerals are used for identical parts or parts with identical actions.

10 [0031] In the first embodiment of the invention, shown in Figs. 1 - 5, an appliance housing 1 is provided that comprises an opening 2 on its front side, into which a change-over magazine 40 can be inserted.

[0032] The change-over magazine contains a plurality of supply cylinders 10-1 to 10-n; in the embodiment shown here, there are 8 such supply cylinders 10. It is evident in the drawings that in this case the supply cylinders 10 have been constructed directly within the change-over magazine or
15 are formed by the magazine itself, and have not been inserted as separate cylinders.

[0033] Each of the supply cylinders 10 comprises a piston 12 that closes the cylinder at one end. In the interior of the supply cylinders 10 a working fluid, in particular Ringer solution, is enclosed in a leakproof manner.

20 [0034] Each supply cylinder communicates with an outlet 13 having a collection channel 45, which in turn is connected to a pressure conduit 20.

[0035] The pistons 12 comprise — as shown in the enlarged section of Fig. 4 — a back-flow barrier 14 that keeps the piston 12 in its final position, i.e. when all the fluid has been expelled, as is known per se for single-use syringes.

25 [0036] After being inserted into the opening 2 of the housing 1, the change-over magazine 40 is locked to a holder 41, so that it is firmly retained within the appliance housing 1.

[0037] Within the housing 1 there are additionally provided actuation devices 30-1 to 30-n, which are shown here as hydraulic cylinders but can of course also be designed as electrically driven recirculating ball screws or the like.

30 [0038] Each of the actuation devices 30 comprises a plunger 31, which is disposed in the housing 1 in such a way that when the change-over magazine 40 is in position, the actuating plungers 31 are situated opposite the pistons 12 that face them.

[0039] The insertion position, i.e. the position of the components immediately after the change-over magazine 40 has been inserted into the housing 1, is shown in Fig. 1. In this position the collection channel 5 and the pressure conduit 20 are still empty.

[0040] Now when the first actuation device 30-1 is actuated, so that its plunger 31 is driven forward, the plunger — as shown in Fig. 3 — presses the piston 12 into the supply cylinder 10, so that fluid 11 passes through an outlet 13 of the first supply cylinder 10-1 into the collection channel 45 and through the latter into the pressure conduit 20, which conducts it to the working instrument (not shown).

[0041] As soon as the first supply cylinder 10-1 is empty (see Fig. 4), another supply cylinder 10-n is “triggered” to deliver its stored working fluid 11 by way of the plunger 31 of the associated actuation device 30-n. As this occurs, the piston 12 of the emptied supply cylinder 10-1 is retained in its final position by the back-flow barrier 14, so that any force exerted by fluid emerging from the supply cylinder 10-n and present in the collection channel 45 cannot cause this piston 12 to be pushed backward.

[0042] The embodiment shown in Figs. 6 and 7 differs from that according to Figs. 1 - 5 in particular in that the change-over magazine 40 comprises chambers 42 into which individual supply cylinders 10 can be inserted as separate “structural components”. In this arrangement the change-over magazine 40 can be rotated about its axis, allowing supply cylinders 10-1 to 10-n to be consecutively positioned so that their outlet 13 is connected to a sealing device 43, which mediates a leakproof connection between the associated supply cylinder 10 and the pressure conduit 20. These drawings show an opening needle 44, which is provided to open closure devices (not shown) on the outlets 13 of the supply cylinders 10; this needle opens the closure device of the relevant supply cylinder 10 whenever the sealing device 43 is pressed against the outlet 13 of the supply cylinder 10. Exchanging of the supply cylinders 10 by rotation of the change-over magazine 40 thus corresponds somewhat to the replacement of cartridges in (or at the entrance to) the barrel of a revolver.

[0043] Figure 8 shows a — highly schematic — control means for the appliance according to Figs. 1 - 5.

[0044] This control means comprises a computer 25 that is in controlling communication with the actuation devices 30-1 to 30-n. The plungers 31 of the actuation devices 30-1 to 30-n, which in the present case are constructed as electromotor drives (e.g., with recirculating ball screws), exert pressure on the pistons 12 of the supply cylinders 10. The force thus employed can in this embodiment be controlled by the current with which the electromotors $M_1 - M_n$ are driven by the computer 25.

[0045] The outlets of the supply cylinders 10 are connected to the collection channel 45.

Between the various supply cylinders 10 and the collection channel 45 are provided back-flow barriers 14, here constructed as back-flow valves, disposed in such a way that the pressure in the collection channel 45 can in no case have an effect on a piston 12 that at the moment is not being actuated with the corresponding force.

[0046] Between the collection channel 45 and the pressure conduit 20 leading to a working instrument 5, a ventilation device 46 is provided.

[0047] In addition path sensors 32 are provided, which send a signal to the computer 25 at least when the associated plunger 31 has reached its final position.

[0048] With the arrangement shown in Fig. 8 it is now possible to drive the actuation devices 30-1 to 30-n in such a way that the supply cylinders can be emptied one after another, and even in such a way that their emptying periods overlap, so that the operator is not disturbed by fluctuations in pressure of the working fluid.

[0049] From the above it will be evident that a combination of the individual characteristics explained here is readily possible. For example, the magazine shown in Figs. 6 and 7 can also be replaced by one according to Fig. 5 (to be used only once). Control by the computer 25 shown here can of course be replaced by provision of a corresponding cam-disk mechanism.

List of reference numerals

	1	Appliance housing
	2	Opening
	5	Working instrument
5	10	Supply cylinder
	11	Fluid
	12	Piston
	13	Outlet
	14	Back flow barrier
10	20	Pressure conduit
	25	Computer
	30	Actuation device
	31	Plunger
	32	Path sensor
15	40	Change over magazine
	41	Holder
	42	Chamber
	43	Sealing device
	44	Opening needle
20	45	Collection channel
	46	Ventilation device
	50	Change over device

[0050] It will be appreciated by those skilled in the art that changes could be made to the
embodiments described above without departing from the broad inventive concept thereof. It is
25 understood, therefore, that this invention is not limited to the particular embodiments disclosed, but
it is intended to cover modifications within the spirit and scope of the present invention as defined
by the appended claims.

CLAIMS

We claim:

1. Appliance for water-jet surgery, comprising a plurality of supply cylinders ~~(10)~~ in which is stored and pistons arrangements each defining an outlet and adapted to store a
5 working fluid (11) that can be expelled, by means of a the piston (12), through an outlet
(13) into said outlet; a pressure conduit (20), in communication with said outlets and into
which said working fluid is expelled; at least one actuation device (30) to actuate the piston
(12), and pistons; and a change-over device (50) to shift the actuation from the piston (12)
10 of one supply cylinder (10-1) to the piston (12) of another supply cylinder (10-n), so in
order that, in use, the working fluid (11) can be ejected into the pressure conduit (20) from
consecutively emptied emptying supply cylinders (10).

2. Appliance according to Claim 1, ~~characterized in that the~~ wherein said
change-over device (50) ~~is designed so adapted such that the~~ consecutive actuation periods
of ~~actuation each~~ of the pistons (12) ~~can overlap one another, with the result in~~
15 order that expulsion of the fluid (11) into the said pressure conduit (20) is uninterrupted.

3. Appliance according to ~~one of the preceding claims,~~
~~characterized by~~ claim 1, wherein a sealing device (43) to seal the is provided to
provide a leak proof connection to each fluid outlet (13).

4. Appliance according to ~~one of the preceding claims,~~
20 ~~characterized in that~~ claim 1, wherein a plurality of actuation devices (30-1) is
provided.

5. Appliance according to ~~one of the preceding claims,~~
~~characterized in that the~~ pistons (12) comprise claim 1, wherein each of said
pistons comprises a back-flow barriers (14) barrier such that, after a said piston (12) has
25 reached a position in which the it has expelled said working fluid (11) has been
expelled, the from its associated cylinder, said piston cannot be pushed back into a previous
position.

6. ~~Appliance according to one of the preceding claims, characterized in that at the outlet (13) a preferably~~claim 1, wherein an irreversibly openable transport gasket is provided at said outlet of each cylinder.

5 7. ~~Appliance according to one of the preceding claims, characterized by~~claim 1, wherein a change-over magazine (40) is provided to receive a group of supply cylinders (10) cylinder and piston arrangements.

8. ~~Appliance according to Claim 7, characterized in that the~~wherein said change-over magazine (40) comprises~~defines~~chambers (42) that closely surround said the supply cylinders (10).

10 9. ~~Appliance according to one of the claims 7 or 8, characterized in that~~claim 7, wherein collection devices are provided in the change-over magazine (40) there are provided collection devices (45) to conduct working fluid (11) from several~~said~~supply cylinders (10) to the~~said~~pressure conduit (20).

15 10. ~~Appliance according to one of the preceding claims, characterized by~~claim 1, wherein ventilation devices (46) are provided for the preferably simultaneous removal of air from conduit sections located between the outlets (13) of the supply cylinders (10) and the pressure conduit (20).

11. ~~Appliance according to Claim 10, characterized in that the~~wherein ventilation devices are disposed in a change-over magazine (40).

20 12. ~~Appliance according to one of the claims 7 to 11, characterized in that the~~claim 7, wherein said change-over magazine (40) is irreversibly connected to the pressure conduit (20), to form a single-use unit.

ABSTRACT OF THE DISCLOSURE

An appliance for water-jet surgery is ~~proposed, which comprises~~ provided that includes a plurality of supply cylinders in cylinder and piston arrangements in each of which is stored a working fluid that can be expelled, by means of ~~a~~ the piston, through an outlet into a pressure conduit. At least one actuation device is provided to actuate the piston of ~~the~~ each supply cylinder. By means of a change-over device to change the actuation from the piston of one supply cylinder to the piston of another supply cylinder, it is ensured that the working fluid can be expelled into the pressure conduit from consecutively ~~emptied~~ emptying supply cylinders. As a result, an apparatus with a small structure that is achieved by simple means is disclosed.